



## DG4LN

### Generator set

Frequency	(Hz)	60
Rated power	(kW)	4.0 ( 5.36 HP )
DC output	(V-A)	12-8.3
Rated voltage	(V)	120 / 240
Power factor	(cos φ)	1.0
Phase type		Single phase
Excitation		Self-excitation voltage
Dimensions (L X W X H)	(mm)	845 X 530 X 705 ( 33.3 X 20.9 X 27.8 in. )
Dry weight	(kg)	138 ( 304 lbs )
Note		LN: Silent and electric start

Model		ETQ178FG
Type		Single-cylinder, vertical, 4-stroke, air-cooled, direct injection diesel engine
Bore X Stroke	(mm)	78 X 62 ( 3.07 X 2.44 in. )
Displacement	(cc)	296 ( 18.1 cu.in. )
Speed	(rpm)	3600
Maximum output	(kW)	4.9 ( 6.6 HP )
Continuous output	(kW)	4.4 ( 5.9 HP )
Fuel tank capacity	(L)	15 ( 3.96 USgal )
Lube-oil capacity	(L)	1.1 ( 37.17 OZ. )

Engine

## DG6LN

### Generator set

Frequency	(Hz)	60
Rated power	(kW)	6.0 ( 8.04 HP )
DC output	(V-A)	12-8.3
Rated voltage	(V)	120 / 240
Power factor	(cos φ)	1.0
Phase type		Single phase
Excitation		Self-excitation voltage
Dimensions (L X W X H)	(mm)	920 X 530 X 705 ( 36.2 X 20.9 X 27.8 in. )
Dry weight	(kg)	160 ( 352 lbs )
Note		LN: Silent and electric start

Model		ETO186FG
Type		Single-cylinder, vertical, 4-stroke, air-cooled, direct injection diesel engine
Bore X Stroke	(mm)	86 X 70 ( 3.39 X 2.76 in. )
Displacement	(cc)	406 ( 24.78 cu.in. )
Speed	(rpm)	3600
Maximum output	(kW)	7.34 ( 9.85 HP )
Continuous output	(kW)	6.6 ( 8.85 HP )
Fuel tank capacity	(L)	15 ( 3.96 USgal )
Lube-oil capacity	(L)	1.65 ( 55.75 OZ. )

Engine



ETQ PRODUCTS HAVE PASSED EPA AND CARB STANDARD.

EASTERN TOOLS & EQUIPMENT, INC. TEL:1-626-960-6299 FAX:1-626-960-6244 WEB SITE:<http://www.easterntools.com>